



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **01106466 A**(43) Date of publication of application: **24.04.89**

(51) Int. Cl.


H01L 27/12**H01L 21/74**(21) Application number: **62263345**(71) Applicant: **FUJITSU LTD**(22) Date of filing: **19.10.87**(72) Inventor: **GOTO, HIROSHI****(54) MANUFACTURE OF SEMICONDUCTOR DEVICE****(57) Abstract:**

PURPOSE: To form a buried high impurity concentration layer easily and facilitate a stable etching process after a support substrate is bonded by a method wherein a high impurity concentration layer is formed on the support substrate with an insulating film between the then a low impurity concentration layer is formed.

CONSTITUTION: An n^- type layer 21 which corresponds to a low impurity concentration layer is formed on an n^+ type diffused layer 18 by an epitaxial growth method as an element region. After a resist film 22 is applied to the n^- type layer 21 and patterned to have a required pattern, the diffused layer 18 and the n^- type layer 21 are respectively subjected to anisotropic etching by using the resist film 22 as a mask. If the resist film 22 is removed, trenches 23 and 24 are formed at the parts which are not covered with the resist film 22. Then an SiO_2 layer 25 is formed on the surface and in the trenches 23 and 24. By etching back the surface for levelling, an island region is formed with the SiO_2 layer 25. Thus a bipolar transistor which has a P-type base region 26 formed in the n^- type layer 21 and an n^+ type

emitter region 27 and an n^+ type collector region formed in a p-type region.

COPYRIGHT: (C)1989,JPO&Japio



AL